

*** SPARE PART*** SIMATIC S7-200, CPU 222 COMPACT UNIT,
DC POWER SUPPLY 8 DI DC/6 DO DC 4 KB CODE/2 KB DATA,
PROFIBUS DP EXTENDABLE

Supply voltage

Rated value (DC)

- 24 V DC

Yes

Load voltage L+

- Rated value (DC)
- permissible range, lower limit (DC)
- permissible range, upper limit (DC)

24 V

20.4 V

28.8 V

Input current

Inrush current, max.

10 A; at 28.8 V

from supply voltage L+, max.

500 mA; 85 mA to 500 mA, output current for expansion modules
(5 V DC) 340 mA

Encoder supply

24 V encoder supply

- 24 V
- Short-circuit protection
- Output current, max.

Yes; permissible range: 15.4 to 28.8 V

Yes; electronic at 600 mA

180 mA

Power loss

Power loss, typ.

5 W

Memory

Number of memory modules (optional)

1; pluggable memory module, content identical with integral
EEPROM

Work memory

- integrated (for program)
- integrated (for data)

4 kbyte

2 kbyte

Backup

- present

Yes; Program: Entire program maintenance-free on integral
EEPROM, programmable via CPU; data: Entire DB 1 loaded from
PG/PC maintenance-free on integral EEPROM, current values of
DB 1 in RAM, retentive memory bits, timers, counters, etc.
maintenance-free via high-performance capacitor; optional battery
for long-term buffering

Battery

Backup battery

- Backup time, max.

50 h; (min. 8 h at 40 °C); 200 days (typ.) with optional battery module

CPU processing times

for bit operations, max.

0.37 µs

Counters, timers and their retentivity

S7 counter

- Number

256

Retentivity

— adjustable

Yes; via high-performance capacitor or battery

— lower limit

1

— upper limit

256

Counting range

— lower limit

0

— upper limit

32 767

S7 times

- Number

256

Retentivity

— adjustable

Yes; via high-performance capacitor or battery

— upper limit

65

Time range

— lower limit

1 ms

— upper limit

54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min

Data areas and their retentivity

Flag

- Number, max.

32 byte

- Retentivity available

Yes; M 0.0 to M 31.7

- of which retentive with battery

0 to 255, via high-performance capacitor or battery, adjustable

- of which retentive without battery

0 to 112 in EEPROM, adjustable

Hardware configuration

Number of expansion units, max.

2; Only expansion modules of the S7-22x series can be used. Due to the limited output current, the use of expansion modules may be limited.

connectable programming devices/PCs

SIMATIC PG/PC, standard PC

Expansion modules

- Analog inputs/outputs, max.

10; max. 8 inputs and 2 outputs (EM) or max. 0 inputs and 4 outputs (EM)

- Digital inputs/outputs, max.

78; max. 40 inputs and 38 outputs (CPU + EM)

- AS-Interface inputs/outputs, max.

31; AS-Interface slaves (CP 243-2)

Digital inputs

Number of digital inputs

8

Source/sink input	Yes; optionally, per group
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	min. 15 V
Input current	
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; all
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes; I 0.0 to I 0.3
for technological functions	
— parameterizable	Yes; (E 0.0 to E 0.5) 30 kHz
Cable length	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m; not for high-speed signals
Digital outputs	
Number of digital outputs	6; Transistor
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	1 W
Switching capacity of the outputs	
• with resistive load, max.	0.75 A
• on lamp load, max.	5 W
Output voltage	
• for signal "1", min.	20 V DC
Output current	
• for signal "1" rated value	750 mA
• for signal "0" residual current, max.	10 µA
Output delay with resistive load	
• "0" to "1", max.	15 µs; of the standard outputs, max. (Q0.2 to Q0.5) 15 µs; of the pulse outputs, max. (Q0.0 to Q0.1) 2 µs
• "1" to "0", max.	100 µs; of the standard outputs, max. (Q0.2 to Q0.5) 100 µs; of the pulse outputs, max. (Q0.0 to Q0.1) 10 µs
Parallel switching of two outputs	
• for uprating	Yes
Switching frequency	
• of the pulse outputs, with resistive load, max.	20 kHz; Q0.0 to Q0.1
Total current of the outputs (per group)	
all mounting positions	

— up to 40 °C, max.	4.5 A
horizontal installation	
— up to 55 °C, max.	4.5 A
Cable length	
• shielded, max.	150 m
• unshielded, max.	150 m
Analog inputs	
Number of analog potentiometers	1; Analog potentiometer; resolution 8 bit
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Protocols	
• MPI	Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
• PPI	Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s
• serial data exchange	Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbps; the PC/PPI cable can also be used as RS 232/RS 485 converter
MPI	
• Transmission rate, min.	19.2 kbit/s
• Transmission rate, max.	187.5 kbit/s
Integrated Functions	
Number of counters	4; High-speed counters (30 kHz each), 32 bit (incl. sign), can be used as up/down counters or for connecting 2 incremental encoders with 2 pulse trains offset by 90° (max. 20 kHz (A/B counters)); parameterizable enable and reset input; interrupt facilities (incl. call of subroutine with any content) when the setpoint is reached; reversal in counting direction, etc.
Counting frequency (counter) max.	30 kHz
Number of alarm inputs	4; 4 rising edges and/or 4 falling edges
Number of pulse outputs	2; High-speed outputs, 20 kHz, with interrupt option; pulse-width and frequency modulation option
Limit frequency (pulse)	20 kHz

Potential separation	
Potential separation digital inputs	
• between the channels	Yes
• between the channels, in groups of	4
Potential separation digital outputs	
• between the channels	Yes; Optocoupler
• between the channels, in groups of	6
Permissible potential difference	
between different circuits	500 V DC between 24 V DC and 5 V DC
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	55 °C
• vertical installation, min.	0 °C
• vertical installation, max.	45 °C
Air pressure acc. to IEC 60068-2-13	
• permissible range, lower limit	860 hPa
• permissible range, upper limit	1 080 hPa
Relative humidity	
• Operation, min.	5 %
• Operation, max.	95 %; RH class 2 in accordance with IEC 1131-2
Configuration	
Programming	
• Command set	Bit logic instructions, compare instructions, timer instructions, counter instructions, clock instructions, transmissions instructions, table instructions, logic instructions, shift and rotate instructions, conversion instructions, program control instructions, interrupt and communications instructions, logic stack instructions, integer maths, floating-point math instructions, numerical functions
• Program processing	free cycle (OB 1), interrupt-controller, time-controlled (1 to 255 ms)
• Program organization	1 OB, 1 DB, 1 SDB subroutines with/without parameter transfer
• Number of subroutines, max.	64
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
Know-how protection	

- User program protection/password protection

Yes; 3-stage password protection

Connection method

Plug-in I/O terminals

No

Dimensions

Width

90 mm

Height

80 mm

Depth

62 mm

Weights

Weight, approx.

270 g

last modified:

07/05/2019