



Digital inputs	
Number of digital inputs	8
Number of NAMUR inputs	8
Input voltage	
• Type of input voltage	DC
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	2.8 ms
— at "0" to "1", max.	3.5 ms
— at "1" to "0", min.	2.8 ms
— at "1" to "0", max.	3.5 ms
Cable length	
• shielded, max.	500 m
Encoder	
Number of connectable encoders, max.	8
Connectable encoders	
• NAMUR encoder	Yes
NAMUR encoder	

- Input current for signal "0", max. 1.2 mA
- Input current for signal "1", min. 2.1 mA

Interrupts/diagnostics/status information

Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	No
Diagnostic messages	
• Diagnostic information readable	Yes
• Short-circuit	Yes; R load < 150 ohms with NAMUR sensor/sensor and NAMUR changeover contact/sensor to DIN 19234
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes

Integrated Functions

Frequency measurement	Yes; (Gate time) 50 ms; 200 ms; 1 s
Number of frequency meters	2

Counter

Number of counter inputs	2; normal and periodic count function
Input frequency, max.	5 kHz; with a cable length of 20 m: 5 kHz; with a cable length of 100 m: 1 kHz; with a cable length of 200 m: 500 Hz

Potential separation

Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes

Permissible potential difference

between different circuits	60 V DC/30 V AC
----------------------------	-----------------

Standards, approvals, certificates

CE mark	Yes
Use in hazardous areas	
• Type of protection acc. to EN 50020 (CENELEC)	II2 G (1) GD Ex ib[ia] IIC T4 and I M2 Ex ib[ia] I
• Type of protection acc. to KEMA	04 ATEX 1248

Dimensions

Width	30 mm
Height	129 mm
Depth	136.5 mm

Weights

Weight, approx.	255 g
-----------------	-------

last modified:

05/14/2018