

SIMATIC S7-300, CPU 312 Central processing unit with MPI, Integr. power supply 24 V DC, Work memory 32 KB, Micro Memory Card required



Figure similar

General information	
HW functional status	01
Firmware version	V3.3
Engineering with	
• Programming package	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.2 + SP1 or higher with HSP 218
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
• Repeat rate, min.	1 s
Input current	

Current consumption (rated value)	650 mA
Current consumption (in no-load operation), typ.	140 mA
Inrush current, typ.	3.5 A
I^2t	1 A ² ·s

Power loss

Power loss, typ.	4 W
------------------	-----

Memory

Work memory	
• integrated	32 kbyte
• expandable	No
• Size of retentive memory for retentive data blocks	32 kbyte
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 y
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data

CPU processing times

for bit operations, typ.	0.1 µs
for word operations, typ.	0.24 µs
for fixed point arithmetic, typ.	0.32 µs
for floating point arithmetic, typ.	1.1 µs

CPU-blocks

Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
• Number, max.	1 024; Number range: 1 to 16000
• Size, max.	32 kbyte
FB	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	32 kbyte
FC	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	32 kbyte
OB	
• Description	see instruction list
• Size, max.	32 kbyte
• Number of free cycle OBs	1; OB 1

• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	4; OB 80, 82, 85, 87
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	16
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	All (incl. memory bits, times, counters)
Flag	
• Number, max.	256 byte

• Retentivity available	Yes; MB 0 to MB 255
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	32 kbyte; Max. 2 KB per block
Address area	
I/O address area	
• Inputs	1 024 byte
• Outputs	1 024 byte
Process image	
• Inputs	1 024 byte
• Outputs	1 024 byte
• Inputs, adjustable	1 024 byte
• Outputs, adjustable	1 024 byte
• Inputs, default	128 byte
• Outputs, default	128 byte
Digital channels	
• Inputs	256
— of which central	256
• Outputs	256
— of which central	256
Analog channels	
• Inputs	64
— of which central	64
• Outputs	64
— of which central	64
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
• integrated	0
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	4
Rack	
• Racks, max.	1
• Modules per rack, max.	8

Time of day	
Clock	
• Software clock	Yes
• retentive and synchronizable	No; Buffered: No, Can be synchronized: Yes
• Deviation per day, max.	10 s; Typ.: 2 s
• Behavior of the clock following POWER-ON	The clock continues at the time of day it had when power was switched off
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
• in AS, slave	No
Digital inputs	
Number of digital inputs	0
Digital outputs	
Number of digital outputs	0
Analog inputs	
Number of analog inputs	0
Analog outputs	
Number of analog outputs	0
Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	1; MPI
Number of RS 422 interfaces	0
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA
Functionality	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No

• Point-to-point connection	No
MPI	
• Transmission rate, max.	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes
Communication functions	
PG/OP communication	Yes
Data record routing	No
Global data communication	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	8
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte; With PUT/GET
• User data per job (of which consistent), max.	240 byte; as server
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	6
• usable for PG communication	5
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	5

- usable for OP communication
 - reserved for OP communication
 - adjustable for OP communication, min.
 - adjustable for OP communication, max.
- usable for S7 basic communication
 - reserved for S7 basic communication
 - adjustable for S7 basic communication, min.
 - adjustable for S7 basic communication, max.

5
1
1
5
2
0
0
2

S7 message functions

Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300

Test commissioning functions

Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4

Status/control

- Status/control variable
- Variables
- Number of variables, max.
 - of which status variables, max.
 - of which control variables, max.

Yes
Inputs, outputs, memory bits, DB, times, counters
30
30
14

Forcing

- Forcing
- Forcing, variables
- Number of variables, max.

Yes
Inputs, outputs
10

Diagnostic buffer

- present
- Number of entries, max.
 - adjustable
 - of which powerfail-proof
- Number of entries readable in RUN, max.
 - can be set
 - preset

Yes
500
No
100; Only the last 100 entries are retained
499
Yes; From 10 to 499
10

Service data

- can be read out

Yes

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 60 °C

Configuration

Configuration software

- STEP 7 Yes; V5.2 SP1 or higher with HW update

Programming

- Command set see instruction list
- Nesting levels 8
- System functions (SFC) see instruction list
- System function blocks (SFB) see instruction list

Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- GRAPH Yes
- HiGraph® Yes

Know-how protection

- User program protection/password protection Yes
- Block encryption Yes; With S7 block Privacy

Dimensions

Width	40 mm
Height	125 mm
Depth	130 mm

Weights

Weight, approx.	270 g
-----------------	-------

last modified: 04/29/2018