

SIMATIC S7-300, Front connector for signal modules with spring-loaded contacts, 20-pole



General information

Product type designation	Front connector
--------------------------	-----------------

Ambient conditions

Ambient temperature during operation

- | | |
|--------|-------|
| • min. | 0 °C |
| • max. | 60 °C |

Ambient temperature during storage/transportation

- | | |
|--------|--------|
| • min. | -40 °C |
| • max. | 70 °C |

Accessories

belongs to product	S7-300
--------------------	--------

Connection method

Connection I/O signals

- | | |
|----------------------------------|--|
| • Connection method | Spring terminals |
| • Number of lines per connection | 1; or combination of 2 conductors of up to 1.5 mm ² (total) in a shared ferrule |

Conductor cross-section in mm ²
--

— Connectable cable cross-sections for massive cables, min.	0.25 mm ²
— Connectable cable cross-sections for massive cables, min.	1.5 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, max.	1.5 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm ²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16
Wire end processing	
— Stripped length of cables, min.	6 mm
— Stripped length of cables, max.	6 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Design A, 5 mm to 7 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Design E, up to 6 mm long
Dimensions	
Width	23 mm
Height	131 mm
Depth	36 mm
Weights	
Weight, approx.	61 g
last modified:	04/29/2018