

6ES7405-0KA01-0AA0

PS405 10A, DC24/48/60V,DC5V/10A

Technical data

SIMATIC S7-400, PS 405 POWER SUPPLY, WIDE RANGE 10A, 24/48/60V DC, 5V/10A DC	
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
• 48 V DC	Yes
• 60 V DC	Yes
permissible range, lower limit (DC)	Static 19.2 V, dynamic 18.5 V
permissible range, upper limit (DC)	Static 72 V, dynamic 75.5 V
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
• Mains buffering according to NAMUR recommendation	Yes
Input current	
Rated value at 24 V DC	4.5 A
Rated value at 48 V DC	2.1 A
Rated value at 60 V DC	1.7 A
Inrush current, max.	18 A; Full width at half maximum 20 ms
Output voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
Output current	
for backplane bus (5 V DC), max.	10 A; 200 mA base load required
for backplane bus (24 V DC), max.	1 A; idling-proof
Short-circuit protection	Yes
Power	
Active power input, typ.	104 W
Power loss	
Power loss, typ.	29 W
Battery	
Backup battery	
• Backup battery (optional)	Yes; 2x lithium AA; 3.6 V / 1.9 Ah
Hardware configuration	
Slots	
• required slots	2
Potential separation	
primary/secondary	Yes
Degree and class of protection	
Equipment protection class	I, with protective conductor
Standards, approvals, certificates	
FM approval	Yes; up to 40 °C: T4
Connection method	
Design of electrical connection	3x 1.5 mm², solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
Dimensions	
Width	50 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	1 400 g
last modified:	08/02/2019
Last changes: 08/08/2019	