

SIMATIC S7-400, CPU 416-3 PN/DP Central processing unit with:
 Work memory 11.2 MB, (5.6 MB code, 5.6 MB data), interfaces: 1st interface MPI/DP 12 Mbit/s, 2nd interface Ethernet/PROFINET 3rd interface plug-in IFM module



Figure similar

General information	
Product type designation	CPU 416-3 PN/DP
HW functional status	05
Firmware version	V5.3
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.4 SP5 or higher
CiR – Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	10 µs; Time per I/O byte
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	No; Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1.2 A
from backplane bus 5 V DC, max.	1.4 A
from backplane bus 24 V DC, max.	300 mA; 150 mA per DP interface

from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	6 W
Power loss, max.	6.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	11.2 Mbyte
<ul style="list-style-type: none"> integrated (for program) 	5.6 Mbyte
<ul style="list-style-type: none"> integrated (for data) 	5.6 Mbyte
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> expandable FEPRM 	Yes; with Memory Card (FLASH)
<ul style="list-style-type: none"> expandable FEPRM, max. 	64 Mbyte
<ul style="list-style-type: none"> integrated RAM, max. 	1 Mbyte
<ul style="list-style-type: none"> expandable RAM 	Yes; with Memory Card (RAM)
<ul style="list-style-type: none"> expandable RAM, max. 	64 Mbyte
Backup	
<ul style="list-style-type: none"> present 	Yes
<ul style="list-style-type: none"> with battery 	Yes; all data
<ul style="list-style-type: none"> without battery 	No
Battery	
Backup battery	
<ul style="list-style-type: none"> Backup current, typ. 	125 μ A; up to 40 °C
<ul style="list-style-type: none"> Backup current, max. 	550 μ A
<ul style="list-style-type: none"> Backup time, max. 	See reference manual, module data, Chapter 3.3
<ul style="list-style-type: none"> Feeding of external backup voltage to CPU 	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	30 ns
for word operations, typ.	30 ns
for fixed point arithmetic, typ.	30 ns
for floating point arithmetic, typ.	90 ns
CPU-blocks	
DB	
<ul style="list-style-type: none"> Number, max. 	10 000; Number range: 1 to 16000
<ul style="list-style-type: none"> Size, max. 	64 kbyte
FB	
<ul style="list-style-type: none"> Number, max. 	5 000; Number range: 0 to 7999
<ul style="list-style-type: none"> Size, max. 	64 kbyte
FC	
<ul style="list-style-type: none"> Number, max. 	5 000; Number range: 0 to 7999

• Size, max.	64 kbyte
OB	
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	8; OB 10-17
• Number of delay alarm OBs	4; OB 20-23
• Number of cyclic interrupt OBs	9; OB 30-38 (shortest cycle that can be set = 500 μ s)
• Number of process alarm OBs	8; OB 40-47
• Number of DPV1 alarm OBs	3; OB 55-57
• Number of isochronous mode OBs	4; OB 61-63
• Number of multicomputing OBs	1; OB 60
• Number of background OBs	1; OB 90
• Number of startup OBs	3; OB 100-102
• Number of asynchronous error OBs	9; OB 80-88
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	24
• additional within an error OB	2
Counters, timers and their retentivity	
S7 counter	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	

— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	16 kbyte; Size of bit memory address area
• Retentivity available	Yes
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; in 1 memory byte
Local data	
• adjustable, max.	32 kbyte
• preset	16 kbyte
Address area	
I/O address area	
• Inputs	16 kbyte
• Outputs	16 kbyte
of which distributed	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	8 kbyte
— DP interface, outputs	8 kbyte
— PROFINET interface, inputs	8 kbyte
— PROFINET interface, outputs	8 kbyte
Process image	
• Inputs, adjustable	16 kbyte
• Outputs, adjustable	16 kbyte
• Inputs, default	512 kbyte
• Outputs, default	512 kbyte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	131 072
— of which central	131 072
• Outputs	131 072
— of which central	131 072

Analog channels	
<ul style="list-style-type: none"> Inputs 	8 192
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — of which central 	8 192
<ul style="list-style-type: none"> Outputs 	8 192
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — of which central 	8 192
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	63
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
<ul style="list-style-type: none"> Number of connectable IMs (total), max. 	6
<ul style="list-style-type: none"> Number of connectable IM 460s, max. 	6
<ul style="list-style-type: none"> Number of connectable IM 463s, max. 	4; IM 463-2
Number of DP masters	
<ul style="list-style-type: none"> integrated 	1
<ul style="list-style-type: none"> via CP 	10; CP 443-5 Extended
<ul style="list-style-type: none"> via IM 467 	4
<ul style="list-style-type: none"> Mixed mode IM + CP permitted 	No; IM 467 not suitable for use with CP 443-5 Ext. and CP 443-1 EX4x, EX20, GX20 (in PROFINET IO mode)
<ul style="list-style-type: none"> via interface module 	1; IF 964-DP
<ul style="list-style-type: none"> Number of pluggable S5 modules (via adapter capsule in central device), max. 	6
Number of IO Controllers	
<ul style="list-style-type: none"> integrated 	1
<ul style="list-style-type: none"> via CP 	4; No mixed operation of CP443-1 EX40 and CP443-1 EX 41/EX20/GX20, max. 4 in central controller
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> FM 	Limited by number of slots or number of connections
<ul style="list-style-type: none"> CP, PtP 	CP 440: Limited by number of slots; CP 441: limited by number of connections
<ul style="list-style-type: none"> PROFIBUS and Ethernet CPs 	14; Of which 10 CPs max. or IMs as DP master, 4 PROFINET controller maximum
Slots	
<ul style="list-style-type: none"> required slots 	2
Time of day	
Clock	
<ul style="list-style-type: none"> Hardware clock (real-time) 	Yes
<ul style="list-style-type: none"> retentive and synchronizable 	Yes
<ul style="list-style-type: none"> Resolution 	1 ms
<ul style="list-style-type: none"> Deviation per day (buffered), max. 	1.7 s; Power off
<ul style="list-style-type: none"> Deviation per day (unbuffered), max. 	8.6 s; For power On
Operating hours counter	

• Number	16
• Number/Number range	0 to 15
• Range of values	SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 ³¹ - 1 hours
• Granularity	1 h
• retentive	Yes

Clock synchronization

• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
• on Ethernet via NTP	Yes; As client
• to IF 964 DP	Yes

Time difference in system when synchronizing via

• Ethernet, max.	10 ms
• MPI, max.	200 ms

Interfaces

Number of RS 485 interfaces	2
Number of other interfaces	0

1. Interface

Interface type	Integrated
Physics	RS 485 / PROFIBUS + MPI
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	MPI: 44, DP: 32

Protocols

• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes

MPI

• Number of connections	44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s

Services

— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes

— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
• Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• Number of connections	32
• GSD file	http://support.automation.siemens.com/WW/view/en/113652
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	No
• Address area, max.	32; Virtual slots
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes; with interface active
— S7 routing	Yes; with interface active

— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	No
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface

Interface type	PROFINET
Physics	Ethernet, 2-port switch, 2*RJ45
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	No
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
Number of connection resources	64

Protocols	
• PROFINET IO Controller	Yes
• PROFINET IO Device	No
• PROFINET CBA	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Open IE communication	Yes
• Web server	Yes; only read function
• Point-to-point connection	No

PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s

Services	
— PG/OP communication	Yes
— Routing	Yes; Routing of PG functions
— S7 communication	Yes
— Isochronous mode	No
— Open IE communication	Yes
— Prioritized startup	Yes
— Number of IO devices with prioritized startup, max.	32
— Number of connectable IO Devices, max.	256
— Of which IO devices with IRT, max.	0

— of which in line, max.	0
— Number of IO Devices with IRT and the option "high flexibility"	256
— of which in line, max.	61
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— IO Devices changing during operation (partner ports), supported	Yes
— Device replacement without swap medium	Yes
— Send cycles	250 µs, 500 µs, 1 ms
— Updating time	250 µs to 512 ms; minimum value dependent on preset communication share for PROFINET I/O, of number of I/O devices and number of configured user data

Address area

— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
— User data consistency, max.	255 byte; Including user data attendant

PROFINET CBA

• acyclic transmission	Yes
• cyclic transmission	Yes

Open IE communication

• Number of connections, max.	62
• Local port numbers used at the system end	0, 20, 21, 25, 80, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535

3. Interface

Interface type	Pluggable interface module (IF)
Plug-in interface modules	IF 964-DP (MLFB: 6ES7964-2AA04-0AB0)
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
automatic detection of transmission rate	No
Number of connection resources	32
Protocols	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
PROFIBUS DP master	
• Number of connections, max.	32
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes

— Routing	Yes; S7 routing
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV0	Yes
— DPV1	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• Number of connections	32
• GSD file	http://support.automation.siemens.com/WW/view/en/113652
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	No
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes
— S7 routing	Yes; with interface active
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	No

— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

Protocols

Open IE communication	
• TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	62
— Data length, max.	32 kbyte
• ISO-on-TCP (RFC1006)	Yes; Via integrated PROFINET interface or CP 443-1 Adv. and loadable FBs
— Number of connections, max.	62
— Data length, max.	32 kbyte; 1452 bytes via CP 443-1 Adv.
• UDP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	62
— Data length, max.	1 472 byte
Web server	
• Number of HTTP clients	5

Isochronous mode

Isochronous operation (application synchronized up to terminal)	Yes; For PROFIBUS only
Equidistance	Yes
Number of DP masters with isochronous mode	2
User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms; 0.5 ms without use of SFC 126, 127
max. cycle	32 ms

Communication functions

PG/OP communication	Yes
• Number of connectable OPs without message processing	63
• Number of connectable OPs with message processing	63; When using alarm_S and alarm_D
Data record routing	Yes

Global data communication

• supported	Yes
• Number of GD loops, max.	16
• Number of GD packets, transmitter, max.	16
• Number of GD packets, receiver, max.	32
• Size of GD packets, max.	54 byte
• Size of GD packet (of which consistent), max.	1 variable

S7 basic communication

• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	1 variable
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
• User data per job (of which consistent), max.	462 byte; 1 variable
S5 compatible communication	
• supported	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
• User data per job, max.	8 kbyte
• User data per job (of which consistent), max.	240 byte
• Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.	64/64
Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
Web server	
• supported	Yes
PROFINET CBA (at set setpoint communication load)	
• Setpoint for the CPU communication load	20 %
• Number of remote interconnection partners	32
• Number of functions, master/slave	150
• Total of all master/slave connections	6 000
• Data length of all incoming connections master/slave, max.	65 000 byte
• Data length of all outgoing connections master/slave, max.	65 000 byte
• Number of device-internal and PROFIBUS interconnections	1 000
• Data length of device-internal und PROFIBUS interconnections, max.	16 000 byte
• Data length per connection, max.	2 000 byte
Remote interconnections with acyclic transmission	
— Sampling frequency: Sampling time, min.	200 ms; Depending on preset communication load, number of interconnections and data length used
— Number of incoming interconnections	500
— Number of outgoing interconnections	500
— Data length of all incoming interconnections, max.	16 000 byte
— Data length of all outgoing interconnections, max.	16 000 byte

— Data length per connection, max.	2 000 byte
Remote interconnections with cyclic transmission	
— Transmission frequency: Transmission interval, min.	1 ms; Depending on preset communication load, number of interconnections and data length used
— Number of incoming interconnections	300
— Number of outgoing interconnections	300
— Data length of all incoming interconnections, max.	4 800 byte
— Data length of all outgoing interconnections, max.	4 800 byte
— Data length per connection, max.	250 byte
HMI variables via PROFINET (acyclic)	
— Number of stations that can log on for HMI variables (PN OPC/iMap)	2x PN OPC/1x iMap
— HMI variable updating	500 ms
— Number of HMI variables	1 500
— Data length of all HMI variables, max.	48 000 byte
PROFIBUS proxy functionality	
— supported	Yes; 32 PROFIBUS slaves max. connectable
— Data length per connection, max.	240 byte; Slave-dependent
Number of connections	
• overall	64
• usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
• usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
• usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
• usable for S7 communication	
— reserved for S7 communication	0
— adjustable for S7 communication, max.	0
• usable for routing	
— reserved for routing	0
— adjustable for routing, max.	0
S7 message functions	
Number of login stations for message functions, max.	63; Max. 63 with ALARM_S and ALARM_D (OPs); max. 12 with ALARM_8 and ALARM_P (e.g. WinCC)
Symbol-related messages	Yes

SCAN procedure	Yes
Program alarms	Yes
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks
Alarm 8-blocks	Yes
<ul style="list-style-type: none"> • Number of instances for alarm 8 and S7 communication blocks, max. 	4 000
<ul style="list-style-type: none"> • preset, max. 	600
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	32
Number of messages	
<ul style="list-style-type: none"> • overall, max. 	1 024
<ul style="list-style-type: none"> • in 100 ms grid, max. 	128
<ul style="list-style-type: none"> • in 500 ms grid, max. 	512
<ul style="list-style-type: none"> • in 1000 ms grid, max. 	1 024
Number of additional values	
<ul style="list-style-type: none"> • with 100 ms grid, max. 	1
<ul style="list-style-type: none"> • with 500, 1000 ms grid, max. 	10
Test commissioning functions	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> • Status/control variable 	Yes; Up to 16 variable tables
<ul style="list-style-type: none"> • Variables 	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
<ul style="list-style-type: none"> • Number of variables, max. 	70; Status/control
Forcing	
<ul style="list-style-type: none"> • Forcing 	Yes
<ul style="list-style-type: none"> • Forcing, variables 	Inputs/outputs, bit memories, distributed I/Os
<ul style="list-style-type: none"> • Number of variables, max. 	512
Diagnostic buffer	
<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • Number of entries, max. 	3 200
<ul style="list-style-type: none"> — adjustable 	Yes
<ul style="list-style-type: none"> — preset 	120
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class A, for use in industrial areas 	Yes
<ul style="list-style-type: none"> • Limit class B, for use in residential areas 	No

Configuration

Configuration software	
• STEP 7	Yes
Programming	
• Command set	see instruction list
• Nesting levels	7
• Access to consistent data in process image	Yes
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Number of simultaneously active SFCs	
— DPSYC_FR	2
— D_ACT_DP	8
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	8
— DP_TOPOL	1
Number of simultaneously active SFBs	
— RDREC	8
— WRREC	8
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	0.9 kg
last modified:	06/21/2018