

Product type designation

PROFIBUS bus terminal 12M

Bus terminal 12M for PROFIBUS, Transmission rates 9.6 Kbit/s to 12 Mbit/s, Plug-in cable 1.5 m



Electrical data

Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
-------------------------------	--------------------------

Interfaces

Number of electrical connections	2
<ul style="list-style-type: none"> • for PROFIBUS cables 	
Type of electrical connection	Screw terminals
<ul style="list-style-type: none"> • for PROFIBUS cables 	

Mechanical data

Material / of the enclosure	plastic
-----------------------------	---------

Design, dimensions and weight

Width	50 mm
Height	138 mm
Depth	53 mm
Net weight	360 g
Mounting type	Yes
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	

Standards, specifications, approvals

Certificate of suitability

- UL approval

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

09/29/2018