

Product type designation

PROFIBUS OLM/G12-1300 V4.0
PROFIBUS OLM/G12-1300 V4.0 optical link module with 1 RS485 and 2 glass FOC Interfaces (4 BFOC sockets), 1300 Nm shaft Length for large distances with signaling contact and test port



Transmission rate	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Transfer rate / with PROFIBUS PA	45.45 kbit/s
Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	3
Number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
Number of optical interfaces / for fiber optic cable	2
Design of the optical interface / for fiber optic cable	BFOC port

Optical data	
Damping ratio / of the FOC transmission link for glass FOC with 10/125 µm or 9/125 µm / at 0.5 dB/km / maximum	8 dB
propagation delay [bit]	6.5 bit
Connectable optical power relative to 1 mW for glass FOC with 10/125 µm or 9/125 µm / at 0.5 dB/km	-19 dB
Optical sensitivity relating to 1 mW for glass FOC with 10/125 µm or 9/125 µm / at 0.5 dB/km	-29 dB
Wavelength for glass FOC with 10/125 µm or 9/125 µm / compatible with interface / at 0.5 dB/km	1310 nm
Wire length for glass FOC with 10/125 µm or 9/125 µm / at 0.5 dB/km / maximum	15 km
Signal-Inputs/outputs	
Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / at DC / Rated value	24 V
Supply voltage / at DC	18.8 ... 28.8 V
Product component / fusing at power supply input	Yes
Consumed current / at DC / at 24 V / maximum	0.2 A
Permitted ambient conditions	
Ambient temperature - during operation - during storage - during transport	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP40
Design, dimensions and weight	
Design	compact
Width	39.5 mm
Height	112 mm
Depth	74.5 mm
Net weight	340 g

Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Product functions / Redundancy

Product function / Ring redundancy	Yes
------------------------------------	-----

Standards, specifications, approvals

Standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0003X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• CE marking	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/15/2019