SIEMENS

Data sheet

6GK5005-0GA10-1AB2

SCALANCE XB005G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 5x 10/100/1000 Mbit/s RJ45 ports electrical; Manual available as a download



Product type designation	SCALANCE XB005G
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
 for network components or terminal equipment 	5; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	0
Interfaces / others	
Number of electrical connections	
for power supply	1
Type of electrical connection	
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V

external / minimum	19.2 V
• external / maximum	28.8 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.44 A
Power loss [W]	
• at DC / at 24 V	10.5 W

Permitted ambient conditions	
Ambient temperature	
during operation	-10 +60 °C
during storage	-40 +80 °C
 during transport 	-40 +80 °C
Relative humidity	
• at 25 °C / without condensation / during	95 %
operation / maximum	
Protection class IP	IP20

Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.22 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
wall mounting	Yes
• S7-1500 rail mounting	No

Product functions / management, configuration	
Product function	
 multiport mirroring 	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No

Product functions / Redundancy	
Product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No

(PRP)/Redundant Network Access (RNA)	
Standards, specifications, approvals	
Standard	

FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, for FM

GP. IIC, T4

EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc. • for hazardous zone

KEMA 07ATEX0145 X

UL 60950-1, CSA C22.2 No. 60950-1 • for safety / from CSA and UL

EN 61000-6-4 (Class B) • for emitted interference

EN 61000-6-2 • for interference immunity

Standards, specifications, approvals / CE

Certificate of suitability / CE marking

Yes

Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability EN 61000-6-2, EN 61000-6-4

• C-Tick

 KC approval Yes

Standards, specifications, approvals / product conformity

MTBF 139 y

Internet-Link

• to website: Selector SIMATIC NET **SELECTION TOOL**

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

02/06/2019 last modified: