

SIMATIC NET, CP 243-2 Communications processor for Connection of SIMATIC S7-22X to AS-Interface with Masterprofile M0E/M1E according to AS-i specification 2.11



General technical data:

Product designation		AS-Interface Master
Product type designation		CP 243-2
Protection class IP		IP20
Type of electrical connection of the AS-interface		Screw-type connection
Type of voltage supply		via backplane bus
Operating condition separate power supply 24 V		No
Consumed current		
• from profile conductors of the AS-interface		
— at 30 V maximum	mA	100
• from backplane bus maximum	mA	220
Power loss [W]	W	3.7
Insulation voltage rated value	V	500
Product function suitable for AS-i Power24V		No
Product feature redundancy capability		No
Product function		
• web-based management		No
• Diagnostics via email		No
• Galvanic isolation		Yes

Display version		PWR, APF, CER, AUP, CM, SF
Type of configuration of the AS-interface		Set pushbutton on device, command interface

Communication/ Protocol:

Version of the AS-interface specification		V 2.11
AS-interface master profile is supported		M3 (in acc. with AS-interface specification V 2.1)
Type of data transmission		S7-200 backplane bus
Number of units per CPU maximum		2
Number of interfaces		
• as AS-interface		1
• acc. to RS 485		0
• acc. to Industrial Ethernet		0
• acc. to PROFINET		0
• acc. to wireless		0
• acc. to USB		0
• other		0
Product component optical interface		No
Protocol is supported		
• ASIsafe (Safety at work) protocol		No
• PROFIsafe protocol		No
• PROFIBUS protocol		No
• PROFINET IO protocol		No
• PROFINET CBA protocol		No
• TCP/IP		No
• SNMP		No
Standard for wireless communication IEEE 802.11		No

Inputs/ Outputs:

Number of inputs for AS Interface maximum		248
Number of outputs for AS Interface maximum		186
Number of AS-i slaves per AS-Interface maximum		62
Bus cycle time of the AS-interface		
• for 31 slaves	ms	5
• for 62 slaves	ms	10
Access to digital I/O data		via process image/peripheral addresses
Access to analog I/O data		via process image/peripheral addresses

Mechanical data:

Width	mm	71
Height	mm	80
Depth	mm	62
Mounting type		snap-on fastening on 35 mm standard mounting rail or screw fastening using an additional push-in lug

Module format	S7-200 modular system
---------------	-----------------------





Ambient conditions:

Ambient temperature		
• if installed on horizontal mounting rail	°C	0 ... 55
• if installed on vertical mounting rail during operation	°C	0 ... 45
• during transport	°C	-40 ... +70
• during storage	°C	-40 ... +70
Relative humidity at 25 °C during operation maximum	%	95
Installation altitude at height above sea level maximum	m	2 000

Safety related data:

Suitability for use safety-related function		No
Explosion protection marking for intrinsic safety of related equipment		
• EEx ia		No
• EEx ib		No
Explosion protection category for gas		none
Explosion protection category for dust		none

Certificates/ approvals:

General Product Approval	EMC	Declaration of Conformity	Shipping Approval
			
	C-Tick	EG-Konf.	GL

[Miscellaneous](#)



PRS

other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)


<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=6GK7243-2AX01-0XA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6GK7243-2AX01-0XA0>



last modified:

02/19/2019