

### Product type designation

### CP 5512

Communications processor CP 5512 PC Card (Cardbus, 32 Bit) for connection of a PG or Notebook to PROFIBUS or MPI;



### Transfer rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

#### Number of electrical connections

- at the 1st interface / acc. to PROFIBUS

1

#### Type of electrical connection

- at the 1st interface / acc. to PROFIBUS

9-pin Sub-D socket (RS 485)

### Supply voltage, current consumption, power loss

#### Type of voltage / of the supply voltage

DC

#### Supply voltage

- 1 / from backplane bus

3.3 V

#### Relative symmetrical tolerance / at DC

- at 3.3 V

5 %

#### Consumed current

- 1 / from backplane bus / at DC / maximum

0.52 A

#### Power loss [W]

1.8 W

## Ambient conditions

Ambient temperature	
• during operation	5 ... 45 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00

## Design, dimensions and weights

Module format	PC card Type II CardBus (32 bit)
Width	86 mm
Height	5 mm
Depth	54 mm
Net weight	130 g

## Product features, product functions, product components / general

Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

## Performance data

### Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

### Performance data / PROFIBUS DP

Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
• DPV0	Yes
• DPV1	No
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / total	7808 byte
• of the address area of the outputs / as DP master / total	7808 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte

Software / for DP slave function / required	Yes, SOFTNET-PB DP slave
Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / total	122 byte
• of the address area of the outputs / as DP slave / total	122 byte

#### Performance data / S7 communication

Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8

#### Performance data / multi-protocol mode

Number of configurable connections / per PC station	207
---	-----

#### Product functions / management, configuration, engineering

Configuration software / required	Included in the scope of delivery of the required software product
-----------------------------------	--

#### Product functions / Diagnostics

Product function	
• Port diagnostics	Yes

#### Standards, specifications, approvals

Standard	
• for EMC	2004/108/EC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes

#### Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="http://www.siemens.com/industrial-controls/mall">http://www.siemens.com/industrial-controls/mall</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAX Download Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

#### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

03/30/2020