

SIMATIC DP, interface DP/PA-Link and ET200M IM153-2 HF for extended temperature range for max. 12 S7-300 modules with redundancy capability, Timestamping suitable for isochronous mode
New features: up to 12 modules can be used Slave Initiative for Drive ES and Switch ES Expanded quantity structure for HART auxiliary variables Operation of the 64-channel modules 32 signals / slot +++
Observe compatibility instructions in manual +++

General information	
Product type designation	IM 153-2 HF
Firmware version	V6.0.0
Vendor identification (VendorID)	801Eh
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	650 mA
Inrush current, typ.	3 A
I^2t	0.1 A ² ·s
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	5.5 W
Address area	
Addressing volume	
• Inputs	244 byte
• Outputs	244 byte
Hardware configuration	
Number of modules per DP slave interface, max.	12
Time stamping	
Accuracy	1 ms; 1ms at up to 8 modules; 10ms at up to 12 modules

Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting

Interfaces

Transmission procedure	RS 485
Interface physics, RS 485	Yes
Interface physics, FOC	No

PROFIBUS DP

- | | |
|---|---|
| • Node addresses | 1 to 125 permitted |
| • automatic detection of transmission rate | Yes |
| • Output current, max. | 70 mA |
| • Transmission rate, max. | 12 Mbit/s |
| • SYNC capability | Yes |
| • FREEZE capability | Yes |
| • Direct data exchange (slave-to-slave communication) | Yes; as publisher with all IO, as subscriber with F-IO only |
| • Design of electrical connection of PROFIBUS interface | 9-pin sub D |

1. Interface

PROFIBUS DP slave	
• GSD file	SI05801E.GSG
• automatic baud rate search	Yes

Protocols

Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
------------------------------------	-------------------------

Potential separation

Potential separation exists	Yes
-----------------------------	-----

Isolation

Isolation tested with	Isolation voltage 500 V
-----------------------	-------------------------

Degree and class of protection

IP degree of protection	IP20
-------------------------	------

Ambient conditions

Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m

Configuration

Configuration software	
------------------------	--

- STEP 7

Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file

Dimensions

Width	40 mm
Height	125 mm
Depth	117 mm

Weights

Weight, approx.	360 g
-----------------	-------

last modified: 09/07/2018