

SIMATIC DP, ET 200M INTERFACE FOR MAX. 8 S7-300
MODULES, WITH REDUNDANCY, W. INTEGR. FO INTERFACE
FOR CONFIGURING AN OPTICAL LINE

General information	
Vendor identification (VendorID)	8071h
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V; Ripple included
permissible range, upper limit (DC)	28.8 V; Ripple included
external protection for power supply lines (recommendation)	not necessary
Input current	
Current consumption, max.	500 mA; At 24 V DC
Inrush current, typ.	3.5 A
I^2t	0.1 A ² ·s
Output voltage	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1 A
Power loss	
Power loss, typ.	4.5 W
Time stamping	
Accuracy	10 ms; 10 ms / 3 ms
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128
Time format	RFC 1119 Internet (ISP)
Time resolution	1 ms
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting
Interfaces	
Transmission procedure	FOC, wavelength 660 nm
Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 12 Mbit/s
1. Interface	

automatic detection of transmission rate	Yes
Interface types	
• Design of the connection	Optical, 2 x duplex sockets
PROFIBUS DP slave	
• GSD file	(for DPV1) SIEM8071.GSD; SI018071.GSG (for IM 153-2AB0x); SI028071.GSG (for IM 153-2BB0x)
• automatic baud rate search	Yes
Protocols	
PROFIBUS DP	
• Number of node addresses, max.	1 to 125 permitted
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes; Sender
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m
Configuration	
Configuration software	
• STEP 7	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	360 g
last modified:	07/01/2020