



SCALANCE S602 module for protection of devices and components intrinsic safety automation technology and for protection of industrial communication with firewall; other functions: address conversion (NAT/NAPT), DHCP server, Syslog, symbol. names for IP addresses, PPPoE, DYNDNS, SNMP (V1+V3), global firewall rules

Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
• for internal network	1
• for external network	1
• for DMZ	0
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for internal network	RJ45 port
• for external network	RJ45 port
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
design of the removable storage / C-PLUG	Yes

Signal inputs/outputs	
Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Supply voltage / external	24 V
Supply voltage / external	19.2 ... 28.8 V
Type of voltage / of the supply voltage	DC
Consumed current / maximum	0.5 A
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	Non-replaceable melting fuse (F 3 A / 32 V)
Power loss [W] / at DC / at 24 V / typical	6.72 W
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20
Design, dimensions and weights	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.8 kg
Mounting type	Screw mounting on horizontal and vertical surfaces
Mounting type	
• 35 mm DIN rail mounting	Yes
• S7-300 rail mounting	Yes
• wall mounting	Yes
Product features, product functions, product components / general	
Product function / DynDNS client	Yes
Protocol / is supported / PPPoE	Yes
Product functions / management, configuration, engineering	
Product function	
• symbolic names for IP addresses	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	Yes

Type of configuration	SCT: Security Configuration Tool (included in scope of delivery)
Product functions / Diagnostics	
Product function	
• SysLog	Yes
• Packet Filter Log	Yes
• Audit Log	Yes
• System log	Yes
Product functions / DHCP	
Product function	
• DHCP server - internal network	Yes
Product functions / Routing	
Product function / Static IP routing	Yes
Product functions / Security	
Firewall version	stateful inspection
Type of encryption algorithms / with VPN connection	-
Type of authentication procedure / with VPN connection	-
Type of hashing algorithms / with VPN connection	-
Number of possible connections / with VPN connection	0
Number of network nodes / for internal network / with VPN connection	
• Note	-
Product function	
• Password protection	Yes
• Bandwidth limiting	Yes
• NAT/NAPT	Yes
Product functions / time	
Product function / pass on time synchronization	Yes
Protocol / is supported / NTP	Yes
Product component / Hardware real-time clock	Yes
Product feature / Hardware real-time clock w. battery backup	Yes
Standards, specifications, approvals	
Standard	
• for FM	FM 3611
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA IIT..., KEMA 07 ATEX 0145 X
• for safety / from CSA and UL	UL 60950 / CSA C22.2 No. 60950-00, UL 508 / CSA C22.2 No. 142
• for emitted interference	EN 61000-6-4: 2007

• for interference immunity	EN 61000-6-2: 2005
Certificate of suitability	AS/NZS 2064 (Class A), EN 61000-6-2, EN 61000-6-4, marine classification pending
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Korean Register of Shipping (KRS)	Yes
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No

accessories

Product extension / optional / C-PLUG	Yes
---------------------------------------	-----

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

07/13/2020