## SIEMENS

## Data sheet

product type designation

## 6GK1571-0BA00-0AA0



PC adapter USB A2

PC adapter USB A2 USB adapter (USB V2.0) for connection of a PG/PC or notebook to SIMATIC S7 via PROFIBUS or MPI contain USB cable 5 m, MPI cable 0.3 m can be used under Windows XP/Vista/ Windows 7 32/64 bit and higher.

transfer rate		
transfer rate		
<ul> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9.6 kbit/s 12 Mbit/s	
interfaces		
number of electrical connections		
<ul> <li>at the 1st interface / according to PROFIBUS</li> </ul>	1	
number of interfaces / according to USB	1	
type of electrical connection		
<ul> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9-pin Sub-D socket (RS 485)	
<ul> <li>of the USB interface</li> </ul>	Standard-B socket	
standard for interfaces / USB 2.0	Yes	
supply voltage, current consumption, power loss		
type of voltage / of the supply voltage	DC	
type of voltage supply / optional external power supply	No	
supply voltage		
from USB	5 V	
• note	Supply direct from USB	
relative symmetrical tolerance / at DC		
• at 5 V	5 %	
consumed current		
from USB	0.2 A	
power loss [W]	1 W	
ambient conditions		
ambient temperature		
during operation	0 60 °C	
during storage	-40 +70 °C	
during transport	-40 +70 °C	
relative humidity / at 30 °C / during operation / maximum	95 %	
protection class IP	IP20	
design, dimensions and weights		
module format	USB V2.0 adapter	
width	58 mm	
height	26 mm	
depth	105 mm	
net weight	0.365 kg	
fastening method / 35 mm top hat DIN rail mounting	No	
product features, product functions, product components / general		
number of plug-in cards of same design / plug-in / per PC station	1	

number of units / note	-
product functions / diagnostics	
product function	
<ul> <li>port diagnostics</li> </ul>	Yes
standards, specifications, approvals	
standard	
• for EMC	2004/108/EC
<ul> <li>for safety / from CSA and UL</li> </ul>	cULus, UL 60950-1, CSA22.2
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-3, EN 61000-6-4
for interference immunity	EN 61000-6-1, EN 61000-6-2
certificate of suitability	
CE marking	Yes
• C-Tick	Yes
further information / internet links	
internet link	
• to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul> <li>to website: Image database</li> </ul>	http://automation.siemens.com/bilddb
<ul> <li>to website: CAx-Download-Manager</li> </ul>	http://www.siemens.com/cax
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

8/30/2023 🖸