

SIMATIC S7-400H, CPU 414H central processing unit for S7-400H and S7-400F/FH, 4 interfaces: 1 MPI/DP, 1 DP and 2 for sync modules, 768 KB memory (384 KB data/384 KB program)



Figure similar

Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	Yes
Input current	
from backplane bus 5 V DC, typ.	1.8 A
from backplane bus 5 V DC, max.	2 A
from backplane bus 24 V DC, max.	300 mA; Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface
Power loss	
Power loss, typ.	10 W
Memory	
Work memory	
<ul style="list-style-type: none"> <li>• integrated</li> </ul>	768 kbyte; 384 KB for program; 384 KB for data
<ul style="list-style-type: none"> <li>• expandable</li> </ul>	No
Load memory	
<ul style="list-style-type: none"> <li>• expandable FEPR0M</li> </ul>	Yes; with Memory Card (FEPR0M)

• expandable FEPRAM, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	64 Mbyte
<b>Backup</b>	
• present	Yes
• with battery	Yes; all data
• without battery	No
<b>Battery</b>	
<b>Backup battery</b>	
• Backup current, typ.	75 $\mu$ A
• Backup current, max.	860 $\mu$ A
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC
<b>CPU processing times</b>	
for bit operations, typ.	0.1 $\mu$ s
for word operations, typ.	0.1 $\mu$ s
for fixed point arithmetic, typ.	0.1 $\mu$ s
for floating point arithmetic, typ.	0.6 $\mu$ s
<b>CPU-blocks</b>	
<b>DB</b>	
• Number, max.	4 095; DB 0 reserved
• Size, max.	64 kbyte
<b>FB</b>	
• Number, max.	2 048
• Size, max.	64 kbyte
<b>FC</b>	
• Number, max.	2 048
• Size, max.	64 kbyte
<b>OB</b>	
• Number, max.	see instruction list
• Size, max.	64 kbyte
<b>Nesting depth</b>	
• per priority class	24
<b>Counters, timers and their retentivity</b>	
<b>S7 counter</b>	
• Number	256
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	255

— preset	Z 0 to Z 7
<b>Counting range</b>	
— lower limit	1
— upper limit	999
<b>S7 times</b>	
• Number	256
<b>Time range</b>	
— lower limit	10 ms
— upper limit	9 990 s
<b>IEC timer</b>	
• present	Yes
• Type	SFB
<b>Data areas and their retentivity</b>	
<b>Flag</b>	
• Number, max.	8 kbyte
• Retentivity available	Yes; from MB 0 to MB 8191
• Retentivity preset	MB 0 to MB 15
<b>Address area</b>	
<b>I/O address area</b>	
• Inputs	8 kbyte
• Outputs	8 kbyte
<b>of which distributed</b>	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	6 kbyte
— DP interface, outputs	6 kbyte
<b>Process image</b>	
• Inputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Outputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
<b>Subprocess images</b>	
• Number of subprocess images, max.	8
<b>Digital channels</b>	
• Inputs	65 536
— of which central	65 536
• Outputs	65 536
— of which central	65 536
<b>Analog channels</b>	
• Inputs	4 096
— of which central	4 096

• Outputs	4 096
— of which central	4 096
<b>Hardware configuration</b>	
Number of expansion units, max.	21
Multicomputing	No
<b>Interface modules</b>	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	6; IM 463-2
<b>Number of DP masters</b>	
• integrated	2
• via CP	10
• via IM 467	0
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
<b>Number of operable FMs and CPs (recommended)</b>	
• FM	32; Limited by number of slots and number of connections
• CP, PtP	32; Limited by number of slots and number of connections
• CP, LAN	32; Limited by number of slots and number of connections
<b>Slots</b>	
• required slots	2
<b>Time of day</b>	
<b>Clock</b>	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
<b>Operating hours counter</b>	
• Number	8
<b>Clock synchronization</b>	
• supported	Yes
<b>1. Interface</b>	
Isolated	Yes
<b>Functionality</b>	
• MPI	Yes; Default setting
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
<b>MPI</b>	
• Number of connections	32
• Transmission rate, max.	12 Mbit/s
<b>Services</b>	
— PG/OP communication	Yes
— Global data communication	No

— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
<b>DP master</b>	
• Number of connections, max.	32; of which 1 reserved for PG, 1 for OP
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32; Number of slots, max. 512
<b>Services</b>	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	No
— Equidistance	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	No
<b>Address area</b>	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
<b>2. Interface</b>	
Isolated	Yes
<b>Functionality</b>	
• PROFIBUS DP master	Yes; Default setting
• PROFIBUS DP slave	No
• Point-to-point connection	No
<b>DP master</b>	
• Number of connections, max.	32
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	96
<b>Services</b>	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	No

— Equidistance	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	No
— Direct data exchange (slave-to-slave communication)	No
<b>Address area</b>	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
<b>Communication functions</b>	
PG/OP communication	Yes
<b>Global data communication</b>	
• supported	No
<b>S7 basic communication</b>	
• supported	No
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
<b>S5 compatible communication</b>	
• supported	Yes; via CP and loadable FC
• User data per job, max.	8 kbyte
<b>Standard communication (FMS)</b>	
• supported	Yes; Via CP and loadable FB
• User data per job, max.	Dependent on CP
<b>Number of connections</b>	
• overall	32
• usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
• usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
• usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
• usable for routing	

— reserved for routing	0
— adjustable for routing, max.	0

### S7 message functions

Number of login stations for message functions, max.	16
--	----

### Test commissioning functions

#### Diagnostic buffer

• present	Yes
• Number of entries, max.	3 200
— adjustable	Yes
— preset	120

### Configuration

#### Configuration software

• STEP 7	Yes; V5.0 SP2
----------	---------------

#### Programming

##### Programming language

— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes

#### Know-how protection

• User program protection/password protection	Yes
---	-----

### Dimensions

Width	50 mm
Height	290 mm
Depth	219 mm

### Weights

Weight, approx.	1 070 g
-----------------	---------

**last modified:** 04/06/2018