



SIMATIC DP, ET 200ECO PN, voltage distributor PD 24 V DC; 1x 7/8", 4xM12, Degree of protection IP67

Power loss	
Power loss, typ.	3.5 W
Potential separation	
between the load voltages	Yes
Isolation	
tested with	
<ul style="list-style-type: none"> • 24 V DC circuits 	500 V
<ul style="list-style-type: none"> • Test voltage for interface, rms value [Vrms] 	1 500 V; According to IEEE 802.3
Dimensions	
Width	45 mm
Height	175 mm
Depth	49 mm
Weights	
Weight, approx.	590 g

Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



KC



EMV	For use in hazard-	Marine / Shipping
-----	--------------------	-------------------



[CCS \(China Classification Society\)](#)

last modified:

10/18/2024